

ADARSH BEARINGS PVT. LTD.

E-mail: info@adarshbearings.com Web Site: www.adarshbearings.com

BSG 222 Grease

DESCRIPTION:

BSG 222 is extra high performance lithium based greases for wide variety of application and severe operating conditions. These greases are formulated to provide excellent high temperature performance and resistance to water contamination. They also offer excellent protection against rust and corrosion.

APPLICATION:

It is recommended for bearings and slides in the paper, cement & glass industries where severe conditions exist. It is also suitable for centralized systems and is designed to resist shocks and vibrations. Water washout, water ingress corrosive environment, as in mill applications. Especially on axles, rings and bearings. The operating temperature range is -15°C to 150°C. Also this product will work in ceramic industries and wherever water contamination unavoidable.

B E N E F I T S

Higher Drop Point And Higher Mechanical Stability Under High Temperature

BSG 222 Grease are Offer Excellent Protection Against Rust and Corrosion.

BSG 222 Greases provide Excellent Performance in Antifriction Bearings

BSG 222 Grease is used for Paper Mills, Sugar Mills and Mining Application.



TECHNICAL SPECIFICATION:

SR NO.	CHARACTERISTICS	VALUES
1	NLGI	2
2	Appearance	Blue
3	Worked Penetration @25°C After 60 Strokes, 0.1 mm Unites	265-295
4	Drop Point, °C, ASTM D2265,	270
5	Copper Strip Corrosion, ASTM	1A
6	Water Washout, @79°C, ASTM D1264,	5
7	Water Spray Resistance, ASTM D4049,	20